


TRAVI HEA EN 10025 - EN 10034


HEA BEAMS EN 10025 - EN 10034

Ampia gamma disponibile anche in qualità S355J2



HEA section					peso weight	HEA section					peso weight
HE	H	B	S	E	Kg / Mt	HE	H	B	S	E	Kg / Mt
100	96	100	5,0	8,0	16,7	340	330	300	9,5	16,5	105
120	114	120	5,0	8,0	19,9	360	350	300	10,0	17,5	112
140	133	140	5,5	8,5	24,7	400	390	300	11,0	19,0	125
160	152	160	6,0	9,0	30,4	450	440	300	11,5	21,0	140
180	171	180	6,0	9,5	35,5	500	490	300	12,0	23,0	155
200	190	200	6,5	10,0	42,3	550	540	300	12,5	24,0	166
220	210	220	7,0	11,0	50,5	600	590	300	13,0	25,0	178
240	230	240	7,5	12,0	60,3	650	640	300	13,5	26,0	190
260	250	260	7,5	12,5	68,2	700	690	300	14,5	27,0	204
280	270	280	8,0	13,0	76,4	800	790	300	15,0	28,0	224
300	290	300	8,5	14,0	88,3	900	890	300	16,0	30,0	252
320	310	300	9,0	15,5	97,6	1000	990	300	16,5	31,0	272

Possibilità di taglio a misura, taglio inclinato e **foratura**



PROSIDER