


TRAVI HEM EN 10025 - EN 10034

HEM BEAMS EN 10025 - EN 10034

Ampia gamma disponibile anche in qualità S355J2



HEM section					peso weight	HEM section					peso weight
HE	H	B	S	E	Kg / Mt	HE	H	B	S	E	Kg / Mt
100	120	106	12,0	20,0	41,8	340	377	309	21,0	40,0	248
120	140	126	12,5	21,0	52,1	360	395	308	21,0	40,0	250
140	160	146	13,0	22,0	63,2	400	432	307	21,0	40,0	256
160	180	166	14,0	23,0	76,2	450	478	307	21,0	40,0	263
180	200	186	14,5	24,0	88,9	500	524	306	21,0	40,0	270
200	220	206	15,0	25,0	103	550	572	306	21,0	40,0	278
220	240	226	15,5	26,0	117	600	620	305	21,0	40,0	285
240	270	248	18,0	32,0	157	650	668	305	21,0	40,0	293
260	290	268	18,0	32,5	172	700	716	304	21,0	40,0	301
280	310	288	18,5	33,0	189	800	814	303	21,0	40,0	317
300	340	310	21,0	39,0	238	900	910	302	21,0	40,0	333
320	359	309	21,0	40,0	245	1000	1008	302	21,0	40,0	349

Possibilità di taglio a misura, taglio inclinato e foratura



**PROSIDER**